



The Green Motor Technology Product Portfolio Manual

- 3kw Driving System

I. Board of Director's Message

First thank you for your interest of our products and service. The Green Motor Technology Co.(GA) is an innovative technology company that specializes in developing and manufacturing driving systems for electric vehicles (EV). With two decades plus years of expertise and leadership in the dynamic driving system, GA's AC driving system serves our customers for more than 35 countries and beyond, particularly, some customers won championship in their national competition by adopting our driving system, and we have earned more and more repeated business partners by providing consistent products and shared value with customers. Sincerely I wish you have a pleasant experience with us and please feel free to let us know your concerns.



Dr. Kevin WANG
President

In witness of customer honor

II. Typical Electric Vehicle Performance



GAEV301

Maximum Speed	50km/h	Vehicle size(L*W*H)	2400*1080*1725mm
Endurance mileage	100km	Seats	3
Unloading weight	450kg	Wheelbase	1910mm
Full loading weight	750kg	Front wheel tread	0mm
Maximum slope	20%	Rear wheel tread	1000mm
Noise	<50dB	Tires	145/70R12, 3pcs
Battery	12V120ah*5	Driving system	60V 3kw



GAEV302

Maximum Speed	33km/h	Vehicle size(L*W*H)	3000*1400*1480 mm
Endurance mileage	150km	Seats	4
Unloading weight	650kg	Wheelbase	2175mm
Full loading weight	1050kg	Front wheel tread	1210mm
Maximum slope	20%	Rear wheel tread	1200mm
Noise	<50dB	Tires	175/60R13, 4pcs
Battery	12V100ah*5	Driving system	60V 3kw

III. Driving System

Item	Specification		Picture
Motor	Rated power	3kw	
	Battery voltage	60v	
	Rated frequency	102Hz	
	Rated speed	3000RPM	
	Max. speed	7000RPM	
	Speed sensor	48 Pulse signal	
	Protection grade	IP55	
	Insulation grade	H	
	Max.torque	60 N.m	
	Duty	S2-60min	
	Installation size	Tailor made to customer's size	
	Size	Φ205 * 315mm	
	Net weight	18kg	
	Packing	Wooden box	
HS code	85015200		
Controller assembly (Including controller, key switch, stall switch, accelerator, and wire harness)	Rated voltage	60V DC	
	Working voltage range	65%~135% of rated	
	Rated output current	80A	
	Maximum output current	250A	
	Digital input	8	
	Analog input	2	
	Protection grade	IP65	
	Ambient temperature	-40 ~ 50°C	
	Control mode	Vector control	
	Communication mode	CAN	
	Size (L*W*H)	230*165*75mm	
	Net weight	3kg	
	Packing	Carton	
HS code	85371090		
Rear axle	Ratio	10:1	
	Speed capacity	8000RPM	
	Torque capacity	80N.m	
	Noise	≤65dB	
	Length	Tailor made to customer's size	
	Installation size		
	Leaf spring distance		
	Brake style		
	Hub size		
	Est. net weight	35kg	
	Packing	Wooden box	
	HS code	87085079	

V. Norms and Practice

To improve efficiency and maintain both parties' mutual benefit, you are kindly to read the following norms and practice, which is the integrated part of the agreement we are going to reach.

- 1 Delivery time for standard parts is within 20 days.
- 2 Warranty of driving system is one year. Any damage of the parts by violating the instructions does not belong to the warranty coverage.
- 3 Payment for MOQ (≤ 5 sets) is 100% lump-sum before production, payment beyond MOQ is 30% for prepaid, and balance paid before shipment.
- 4 The actual parts and accessories might be not the same due to the shape of the vehicle, purchased items, country norms, and applicability.
- 5 Not to be reprinted, translated or otherwise reproduced in whole or in part without written permission from Foshan Shunde Green Motor Technology Co., Ltd. All rights reserved.
- 6 Should you ever require assistance or any complaints, all you need to do is to contact our president & global chief service officer (GCSO), Mr. Kevin Wang at kevinwang@greenmotortech.com; or reach his mobile phone at +86 13702349858.
- 7 For more details of our company, please visit <http://www.greenmotortech.com>. Green Motor Technology Co. wish you a safe and pleasant driving trip.