



Shenzhen HDKing Electronics Co., Ltd.

Skype: jerrykung

Mail: jerry@hdking8.com

wechat:13510464687

Price/2K	\$87.50	\$51.50	\$57.50	\$42.40	\$45.60	\$37.60	\$33.50
Model	SDL701	NDL703	JDL702	JDL-601	NDL-601	JDL-506	JDH-503
Picture							
Sensor	5.0Mega Pixels CMOS	5.0Mega Pixels CMOS	5.0Mega Pixels CMOS	4.0Mega Pixels CMOS	4.0Mega Pixels CMOS	5.0Mega Pixels CMOS	4.0Mega Pixels CMOS
Lens	4G FOV=90 with Auto IR Filter	FOV= with Auto IR Filter	4G FOV=90 with Auto IR Filter	4G FOV=90 with Auto IR Filter	4G FOV=90 with Auto IR Filter	4G FOV=90 with Auto IR Filter	4G FOV=90 with Auto IR Filter
PIR Sending Angle		Main PIR 90°	Main PIR 90°	Main PIR 90°	Main PIR 90°	Main PIR 90°	Main PIR 90°
Photo	16MP	30M、24M、20M、16M、12M、8M、5M	24M	24M	24M	24M	16MP
Video	1920x1080/30fps	4K/30fps、2.7K/30fps、1296P/30fps、1080P/30fps、720P/30fps、480P/30fps、	1920*1080/1280x720	1920*1080/1280x720	1920*1080/1280x720	1920*1080/1280x720	1920*1080/1280x720
Long Night Vision Range:	20M with 38pcs IR LED	20M with 38pcs IR LED	20M with 45pcs IR LED	20M with 45pcs IR LED	20M with 45pcs IR LED	20M with 45pcs IR LED	20M with 49pcs IR LED
Fast Triggering time	0.3 Second	0.4Second	0.4Second	0.4Second	0.4Second	0.4Second	0.4 Second
Screen	2.4" COLOR TFT LCD	2.4" COLOR TFT LCD	2.0" COLOR TFT LCD	2.0" COLOR TFT LCD	2.0" COLOR TFT LCD	2.0" COLOR TFT LCD	2.0" COLOR TFT LCD
Long Time Standby Time	Approx. 8 months	Approx.8 months	Approx. 8 months	Approx. 8 months	Approx. 8 months	Approx. 8 months	Approx. 8 months
operating temperature	-20℃ to +60℃	-20℃ to +60℃	-20℃ to +60℃	-20℃ to +60℃	-20℃ to +60℃	-20℃ to +60℃	-20℃ to +60℃
communication	4G Support	/	/	/	/	/	/
wifi	/	Support for Apple Android	Support	Support for Apple Android	Support	/	/
Remote controller	/	Hunting 4K	Support	Mobile phone Bluetooth opens WiFi	Support	/	/
H.264	Support	Mobile phone Bluetooth opens WiFi	Support	/	Support	/	/
Size	165x105x83mm	165x105x83mm	239x105x83mm with 2500mah solar panel battery	135*83*52MM	135*83*52MM	135*83*52MM	135*83*52MM

\$37.60	\$35.40	\$33.50	\$32.30	\$26.50	\$22.60	\$17.50	
JDH-501	JDH-502	DL-2	DH-1	JDL-201	SJDL-201	D1-Solar power bank	
							
5.0Mega Pixels CMOS	4.0Mega Pixels CMOS	4.0Mega Pixels CMOS	2.0Mega Pixels CMOS	2.0Mega Pixels CMOS	2.0Mega Pixels CMOS	OUTPUT	DC-6V/2A
4G FOV=90 with Auto IR Filter	4G FOV=90 with Auto IR Filter	4G FOV=90 with Auto IR Filter	4G FOV=80 with Auto IR Filter	4G FOV=80 with Auto IR Filter	4G FOV=80 with Auto IR Filter	DC Adapter	DC-12V
Main PIR 90°	Main PIR 90°	Main PIR 90°	Main PIR 90°	Main PIR 90°	Main PIR 90°	Battery Capacity	7.4V 2500MAH
20MP	16MP	16MP	14MP	12MP	12MP	Connector	Φ3.5
1920*1080/1280x720	1920*1080/1280x720	1920*1080/1280x720	1920*1080/1280x720	1280x720	1280x720	Over Charge Protection	Support
20M with 45pcs IR LED	20M with 49pcs IR LED	20M with 42pcs IR LED	20M with 42pcs IR LED	15M with 22pcs IR LED	15M with 22pcs IR LED	Over Discharge Protection	Support
0.4 Second	0.4 Second	0.4 Second	0.6 Second	0.4 Second	0.4 Second	Over Current Protection	Support
2.4" COLOR TFT LCD	2.4" COLOR TFT LCD	2.4" COLOR TFT LCD	2.4" COLOR TFT LCD	2.0" COLOR TFT LCD	1.5" Black and white screen	IR LED	Red / Blue (red light indicates adapter input, blue light indicates solar recharge battery; when indoor solar panel outputs, blue light and red light are on at the same time).
Approx. 8 months	Approx. 8 months	Approx. 8 months	Approx. 8 months	Approx. 6 months	Approx. 6 months	Spray-water protected	Yes (Protection Class IP56)
-20°C to +60°C	-20°C to +60°C	-20°C to +60°C	-20°C to +60°C	-20°C to +60°C	-20°C to +60°C	Operating Temperature	-20°C to +60°C
/	/	/	/	/	/	Dimensions	Approx. 148*99*15mm
/	/	/	/	/	/		
/	/	/	/	/	/		
/	/	/	/	/	/		
136*83*55MM	136*83*55MM	136*83*55MM	136*83*55MM	109*75*46MM	109*75*46MM		