




TOJOY

INTERLOCKING TILE

FOR INDOOR & OUTDOOR SPORTS COURT



DOUBLE BUFFER PATTERN



Dimension: 250×250×16.6(mm)

Application: Indoor/outdoor basketball court; Cage football court, volleyball court, tennis court, badminton court; Kindergarten playground, etc...



Elastic surface






Elastic bottom

The advantages of double buffer pattern

- 1、 PP stable frame with 196 pcs suspended balls bring anti-slip surface and make players feel better on foot.
- 2、 All directions cushioning, reach shock absorption up to 30%.
- 3、 TPE material with Ucker type touch down Frame, can reduce the movement of the sport court.
- 4、 Both PP tiels and suspended ball, all color can be customized.

BUSHING FRAME PATTERN





Dimension: 300×300×17(mm)

Frame: A tile averagely supported by 196 pieces of soft bushing feet, and each square is filled by 3,136 pieces of soft bushing feet.

Features: Elastic structure can reduce the movement of court and achieve the 30% shock absorption.

Application: Indoor/outdoor basketball court, Cage football court, volleyball court, tennis court, badminton court, etc...

SHOCK PAD PATTERN




Dimension: 304.8×304.8×17.3(mm)

Shock Pad Quantity: Optional from 36, 48, 72 pieces for each tiles.

Features: Elastic structure can reduce the movement of court and achieve the 28% shock absorption.


Application: Indoor/outdoor basketball court; Cage football court, volleyball court, tennis court, badminton court.

INTERLOCKING WITH SHOCK PAD




CI-13001S

Tile Size: 304.8x304.8mm
Thickness: 14mm




CI-13002S

Tile Size: 304.8x304.8mm
Thickness: 14mm




CI-13003S

Tile Size: 304.8x304.8mm
Thickness: 14mm




CO-13005S

Tile Size: 304.8x304.8mm
Thickness: 14mm



CO-13006S


Tile Size: 304.8x304.8mm
Thickness: 14mm



CO-13007S


Tile Size: 304.8x304.8mm
Thickness: 14mm

INTERLOCKING WITH SHOCK PAD




CO-23002S

Tile Size: 304.8x304.8mm
Thickness: 17.3mm




CO-33001S

Tile Size: 304.8x304.8mm
Thickness: 14mm




CO-43001S

Tile Size: 304.8x304.8mm
Thickness: 14mm




CO-43002S

Tile Size: 304.8x304.8mm
Thickness: 14mm



IF-5055G


Tile Size: 250x250mm
Thickness: 16.6mm



CO-23001S


Tile Size: 300x300mm
Thickness: 17mm

15.24m×30.48m FIBA Basketball Court



Tile Size: 304.8×304.8mm
All Lines are Painted

18.288m×36.576m Tennis Court




Tile Size: 304.8×304.8mm
All Lines are Painted

FOR OUTDOOR SPORTS COURT




CH-1020B

Tile Size: 250x250mm
Thickness: 12mm




CH-1020D

Tile Size: 250x250mm
Thickness: 12mm




CH-1020R

Tile Size: 250x250mm
Thickness: 12mm




IF-3011R

Tile Size: 300x300mm
Thickness: 13mm



IF-3011Y


Tile Size: 300x300mm
Thickness: 13mm



SH-2001B


Tile Size: 250x250mm
Thickness: 13mm

FOR OUTDOOR SPORTS COURT




SH-2001G

Tile Size: 250x250mm
Thickness: 13mm




SH-2002G

Tile Size: 304.8x304.8mm
Thickness: 19mm




SH-2002R

Tile Size: 304.8x304.8mm
Thickness: 19mm




CH-1010B

Tile Size: 400x400mm
Thickness: 15.8mm



CH-1010Y


Tile Size: 400x400mm
Thickness: 15.8mm



IF-1020B

Tile Size: 304.8x304.8mm
Thickness: 15.8mm

FOR OUTDOOR SPORTS COURT




IF-2020G

Tile Size: 300x300mm
Thickness: 13mm




IF-2021H

Tile Size: 300x300mm
Thickness: 13.7mm




IF-2021O

Tile Size: 300x300mm
Thickness: 13.7mm




IF-3010B

Tile Size: 304.8x304.8mm
Thickness: 15.8mm



IF-3011H

Tile Size: 300x300mm
Thickness: 13mm



IF-3020G

Tile Size: 300x300mm
Thickness: 12.7mm

FOR OUTDOOR SPORTS COURT




IF-3022Y

Tile Size: 304.8×304.8mm
Thickness: 16.5mm




IF-3032R

Tile Size: 300×300mm
Thickness: 12.2mm




IF-3044B

Tile Size: 300×300mm
Thickness: 19.5mm




CO-32501DG

Tile Size: 250×250mm
Thickness: 13mm



CO-32501G


Tile Size: 250×250mm
Thickness: 13mm



CO-32501R


Tile Size: 250×250mm
Thickness: 13mm

FOR OUTDOOR SPORTS COURT




CO-32502DG

Tile Size: 250x250mm
Thickness: 13mm




CO-32502R

Tile Size: 250x250mm
Thickness: 13mm




CO-3031

Tile Size: 304.8x304.8mm
Thickness: 15mm




CO-3032

Tile Size: 304.8x304.8mm
Thickness: 15mm



CO-3033


Tile Size: 304.8x304.8mm
Thickness: 15mm



CO-3034


Tile Size: 304.8x304.8mm
Thickness: 15mm

FOR OUTDOOR SPORTS COURT




CO-3035

Tile Size: 304.8×304.8mm
Thickness: 13mm




CO-3036

Tile Size: 304.8×304.8mm
Thickness: 13mm




CO-3037

Tile Size: 304.8×304.8mm
Thickness: 13mm




CO-3038

Tile Size: 304.8×304.8mm
Thickness: 15mm



CO-3039

Tile Size: 304.8×304.8mm
Thickness: 15mm




CO-3040

Tile Size: 304.8×304.8mm
Thickness: 15mm

13.716m×22.86m Multi-Game Court

Tennis/Badminton/Basketball/Volleyball




Tile Size: 304.8×304.8mm
All Lines are Painted

FOR INDOOR SPORTS COURT




CI-3021

Tile Size: 304.8×304.8mm
Thickness: 12mm




CI-3022

Tile Size: 304.8×304.8mm
Thickness: 12mm



CI-3023

Tile Size: 304.8×304.8mm
Thickness: 12mm




CI-3024

Tile Size: 304.8×304.8mm
Thickness: 12mm



CI-3025


Tile Size: 304.8×304.8mm
Thickness: 12mm



CI-3026

Tile Size: 304.8×304.8mm
Thickness: 12mm

FOR INDOOR SPORTS COURT




CI-3027

Tile Size: 304.8x304.8mm
Thickness: 12mm



CI-3028

Tile Size: 304.8x304.8mm
Thickness: 12mm




CI-3029

Tile Size: 304.8x304.8mm
Thickness: 12mm

9.144m×12.288m Multi-Game Court

Paddle Tennis/Badminton/Basketball/Hockey



Tile Size: 304.8×304.8mm
All Lines are Painted

SPECIFICATIONS

Item	Standard	Results
Material	ISO2076	Environmentally friendly recyclable UV-stabilized polypropylene
Size of tile	EN427	Qualified
Thickness of tile	EN428	Qualified
Weight	EN430	Qualified
Point load	QUALIFIED TEST BY TOPJOY	≥ 5 ton/1m ²
Light fastness	EN 14836(>3) ISO 105-B02(1-8) ISO 105-A02(>0,3)	4-5 7-8 4/5
Weather Fastness	ASTM D1435 ASTM G154 Cycle A	4/5
Slip resistance	SSEN-13893 EN13036-4	>0.3 96PTV
Impact resistance	ISO 179/1eA ASTM D746	23°C = 20kJ/m ² ; - 20°C=5kJ/m ² C15KJ/m ²
Fire category	EN ISO 11925-2	Cf1
CE certification	EN 14877	CCSH17082811815
Shock absorbtion	EN 14808/EN 14877	28%
Vertical deformation	EN 14809/EN 14877	3mm
Vertical ball behaviour	EN 12235/EN 14877	93%
Resistance to wear	EN ISO 5470-1/EN 14877	0.1g/1000cycles
Water infiltration rate	EN 12616/EN 14877	Requirement very well achieved



TopJoy Industrial Co.,Ltd.



Head Office Add/ Unit 603, Building 7, No. 2449, Jinhai Rd, Pudong New Area, Shanghai, China.

Factory Add/ Yujiang Industry Park, Yujiang Country, Yingtan City, Jiangxi Province China

Tel/ +86 21 39982788

Fax/ +86 21 39982785

Cell/ +86 18321907513

Email/ info@topjoygroup.com

WhatsApp/ +86 18321907513

Wechat/ TonyTopjoy