



GUANGZHOU AURORA LIGHTING CO., LTD

Website: www.auroralightings.com

Tel:00862028988455 Mob/Wechat/WhatsApp:008618924321586 Email:ivy@auroralightings.com

Office Add:Room 4003,Xiangyun Building,No.1400, North Baiyun Road, Baiyun District,510420, Guangzhou,China

Factory Add:2nd Floor,First Building,Songzilong Industrial Park,Jixianzhuang Village,Yongping Street,Baiyun District,Guangzhou,China



ITEM	PART NO.	PICTURE	DESCRIPTIONS	PRICE	LAMP SIZE (MM)	PACKING (PCS/CTN)	G.W. (KG)
3W Cree Single Row LED Light Bar							
6" 18W	AAL-4018		LED Power: 18-144W Operating Voltage: 10-30 DC Waterproof rate: IP 67 3W high intensity Cree LEDs Body Color: Black,White Color Temperature: 6000K Material:Diecast aluminum housing Lens material:Toughed glass Mounting Bracket: Alu firm bracket Beam: Flood beam pattern(60 degree), 30 degee spot beam optional 50000 hours above life time Dimensions:6-49 inch	\$4.99	51*27*20CM	40	16
13" 36W	AAL-4036			\$8.99	81*27*20CM	40	23
19" 54W	AAL-4054			\$11.99	57*27*20CM	20	18
25" 72W	AAL-4072			\$13.99	72*27*20CM	20	21
31" 90W	AAL-4090			\$16.99	88*27*20CM	20	24
37" 108W	AAL-4108			\$19.99	104*27*20CM	20	28
43" 126W	AAL-4126			\$22.99	120*27*20CM	20	32
49" 144W	AAL-4144			\$24.99	135*27*17CM	12	26
5W Cree Single Row LED Light Bar							
7" 30W	AAL-7030		Voltage: 9-32V LED: 5W Cree LEDs Beam: Spot beam, Flood beam & Combo beam LED color temperature: 5000K, 6500K Working life: 50000 hours Working temperature: -40~ 85°C Waterproof rate: IP67 Material: 6063 aluminum profile, stainless steel bracket, PC Lens.	\$10.99	170*41.6*82	8	
10" 50W	AAL-7050			\$13.99	280*41.6*82	8	
20" 100W	AAL-7100			\$22.99	530*41.6*82	4	
30" 150W	AAL-7150			\$33.99	780*41.6*82	4	
40" 200W	AAL-7200			\$44.99	1030*41.6*82	4	
50" 250W	AAL-7250			\$55.99	1280*41.6*82	4	
60" 300W	AAL-7300			\$66.99	1530*41.6*82	4	
3 Rows Philips LED Light Bar							
22" 120W	AAL-5120		3W each Philip LED Operating Volt: 9-32Volt DC Color temperature: 6000K Operation temperature -40°C~60°C Waterproof rate: IP67 Beam: combo Beam Material: Diecast aluminum housing LENS: unbreakable PC Housing color: Black About 30,000 hours life time	\$22.99	635*98*122	6	20.7
33" 180W	AAL-5180			\$33.99	886*111.5*122	4	19.1
42" 240W	AAL-5240			\$44.99	1137*130.59*122	4	25.5
50" 288W	AAL-5288			\$53.99	1341.2*150.14*122	4	30.5
51" 300W	AAL-5300			\$55.99	1370*150.14*122	4	32.5
5" 54W	AAL-5054S		54W and 108W all for reflector cup,only Spot beam 3w high intensity Philip LEDs Operating Voltage: 10-30V DC Waterproof rate: IP 67 Optional Color: Black,White Color Temperature: 6000K Material:Diecast aluminum housing Lens material: PC Mounting Bracket: Alu firm bracket Beam:Spot/flood/Combo 30000 hours above life time	\$4.99	130.5*80*65	20	15
9" 108W	AAL-5108S			\$8.99	232.51*80*65	12	13
13" 162W	AAL-5162S			\$12.99	334.71*80*65	12	18
17" 216W	AAL-5216S			\$16.99	436.72*80*65	6	11
21" 270W	AAL-5270S			\$20.99	539.33*80*65	6	12
23" 324W	AAL-5324S			\$24.99	589.53*80*65	6	15
25" 378W	AAL-5378S			\$28.99	640.7*80*65	6	17
33" 432W	AAL-5432S			\$32.99	844.71*80*65	4	13
37" 486W	AAL-5486S			\$36.99	946.73*80*65	4	15
41" 540W	AAL-5540S			\$41.99	1048.71*80*65	4	20
49" 648W	AAL-5648S			\$49.99	1253.71*80*65	4	26
3 Rows Side shot Philips LED Light Bar							
7.5" 34W	AAL-CF034T		2 bracket optional 1W high intensity PHILIPS LEDs Operating Voltage: 10-30V DC Waterproof rate: IP 67 Optional Color: Black,White Color Temperature: 6000K Material:Diecast aluminum housing Lens material: PC Mounting Bracket: Alu firm bracket Beam:Combo 30000 hours above life time	\$18.99	192*77.5*92	6	
13.5" 58W	AAL-CF058T			\$21.99	344*77.5*92	6	
21.5" 90W	AAL-CF090T			\$29.99	547*77.5*92	6	
31.5" 130W	AAL-CF130T			\$38.99	801.5*77.5*92	4	
41.5" 170W	AAL-CF170T			\$48.99	1055.8*77.5*92	4	
51.5" 210W	AAL-CF210T			\$58.99	1310.01*77.5*92	4	
4 Rows Philips LED Light Bar							
4" 18W	AAL-6018F		1.5W each Philips LEDs Operating Volt: 10-30Volt DC Color temperature:6000K Operation temperature -40°C~60°C Waterproof rate:IP67 Beam:30°spot beam Material:diecast aluminum housing Mounting Bracket:stainless steel bracket. LENS:PC LENS 30000 hours above life time	\$4.99	130.5*80*65	12	9
6.5" 36W	AAL-6036F			\$7.99	232.51*80*65	12	12.12
9" 54W	AAL-6054F			\$10.99	334.71*80*65	12	15.84
12" 72W	AAL-6072F			\$12.99	436.72*80*65	6	10.8
18" 108W	AAL-6108F			\$16.99	589.53*80*65	6	15.3
22" 126W	AAL-6126F			\$19.99	640.7*80*65	6	16.98
23" 144W	AAL-6144F			\$22.99	844.71*80*65	4	10
32" 180W	AAL-6180F			\$27.99	946.73*80*65	6	24.7
36" 234W	AAL-6234F			\$35.99	1048.71*80*65	4	20
45" 288W	AAL-6288F			\$44.99	1253.71*80*65	4	22

13.5" 84W	AAL-HT084		1w high intensity 3030 LEDs Operating Voltage: 10-30V DC Waterproof rate: IP 67 Optional Color: Black,White Color Temperature: 6000K Material:Diecast aluminum housing Lens material: PC Mounting Bracket: Alu firm bracket Beam:Spot 30000 hours above life time	\$21.99	352.42*77*68.54	6	14.3
21.5" 140W	AAL-HT140			\$35.99	557.02*77*68.54	6	20.7
31.5" 210W	AAL-HT210			\$51.99	812.22*77*68.54	4	19.1
41.5" 280W	AAL-HT280			\$66.99	1067.42*77*68.54	4	24.5
50" 336W	AAL-HT336			\$78.99	1071.42*77*68.54	4	28.4
51" 350W	AAL-HT350			\$85.99	1322.52*77*68.54	4	31
13.5" 84W	AAL-HF084		1w high intensity 3030 LEDs Operating Voltage: 10-30V DC Waterproof rate: IP 67 Optional Color: Black,White Color Temperature: 6000K Material:Diecast aluminum housing Lens material: PC Mounting Bracket: Alu firm bracket Beam:Combo 30000 hours above life time	\$19.99	352.42*77*68.54	6	14.3
21.5" 140W	AAL-HF140			\$32.99	557.02*77*68.54	6	20.7
31.5" 210W	AAL-HF210			\$45.99	812.22*77*68.54	4	19.1
41.5" 280W	AAL-HF280			\$57.99	1067.42*77*68.54	4	24.5
50" 336W	AAL-HF336			\$69.99	1071.42*77*68.54	4	28.4
51" 350W	AAL-HF350			\$74.99	1322.52*77*68.54	4	31
5" 28W	AAL-ST028		1W high intensity Philips LEDs Operating Voltage: 10-30V DC Waterproof rate: IP 67 Optional Color: Black,White Color Temperature: 6000K Material:Diecast aluminum housing Lens material: PC Mounting Bracket: Alu firm bracket Beam:Spot 30000 hours above life time	\$7.99	130.5*80*65	20	15
13" 84W	AAL-ST084			\$15.99	334.71*80*65	12	18
21" 140W	AAL-ST140			\$21.99	539.33*80*65	6	12
25" 168W	AAL-ST168			\$29.99	640.7*80*65	6	17
33" 224W	AAL-ST210			\$36.99	844.71*80*65	4	13
41" 280W	AAL-ST280			\$48.99	1048.71*80*65	4	20
49" 336W	AAL-ST336			\$58.99	1253.71*80*65	4	26
5" 28W	AAL-SF028			\$6.99	130.5*80*65	20	15
9" 56W	AAL-SF056		1w high intensity 3030 LEDs Operating Voltage: 10-30V DC Waterproof rate: IP 67 Optional Color: Black,White Color Temperature: 6000K Material:Diecast aluminum housing Lens material: PC Mounting Bracket: Alu firm bracket Beam:Combo 30000 hours above life time	\$10.99	232.51*80*65	12	13
13" 84W	AAL-SF084			\$13.99	334.71*80*65	12	18
17" 112W	AAL-SF112			\$16.99	436.72*80*65	6	11
21" 140W	AAL-SF140			\$19.99	539.33*80*65	6	12
23" 156W	AAL-SF156			\$23.99	589.53*80*65	6	15
25" 168W	AAL-SF168			\$25.99	640.7*80*65	6	17
33" 224W	AAL-SF224			\$34.99	844.71*80*65	4	13
37" 252W	AAL-SF252			\$38.99	946.73*80*65	4	15
41" 280W	AAL-SF280			\$42.99	1048.71*80*65	4	20
49" 336W	AAL-SF336			\$50.99	1253.71*80*65	4	26
36W	AAL-2T36		With Angle Eye 3w high intensity Cree LEDs Operating Voltage: 10-30V DC Waterproof rate: IP 67 Optional Color: Black,White Color Temperature: 6000K Material:Diecast aluminum housing Lens material: PC Mounting Bracket: Alu firm bracket Beam:Combo 30000 hours above life time	\$16.99	211*73*90	12	
72W	AAL-2T72			\$26.99	376*73*90	6	
108W	AAL-2T108			\$37.99	541*73*90	6	
144W	AAL-2T144			\$46.99	706*73*90	6	
180W	AAL-2T180			\$55.99	871*73*90	4	
216W	AAL-2T216			\$65.99	1036*73*90	4	
252W	AAL-2T252			\$74.99	1201*73*90	4	
288W	AAL-2T288			\$84.99	1366*73*90	4	
324W	AAL-2T324	\$94.99	1531*73*90	4			
2 Rows Side Shot LED Light Bar							
7.5" 66W	AAL-CF066		3W CREE LEDs+0.2W(Blue,Yellow,Red) Operating Voltage: 10-30V DC Waterproof rate: IP 67 Optional Color: Black Color Temperature: 6000K Material:Diecast aluminum housing Lens material: PC Mounting Bracket: Alu firm bracket Beam:Combo 30000 hours above life time	\$21.99	192*77.5*92	6	
13.5" 102W	AAL-CF102			\$32.99	344*77.5*92	6	
21.5" 150W	AAL-CF150			\$48.99	547*77.5*92	4	
31.5" 210W	AAL-CF210			\$65.99	801.5*77.5*92	4	
41.5" 270W	AAL-CF270			\$84.99	1055.8*77.5*92	4	
51.5" 330W	AAL-CF330			\$103.99	1310*77.5*92	4	
Single Row LED Light Bar							
6" 20W	AAL-1020		10W high intensity USA CREE XML LED Voltage:10V-45V DC Color temperature:6000K Housing Material:6063 Diecast aluminum housing Housing color: Black LENS Material: Scratch-resistant import PC Mounting Bracket: Side mount and Base mount Alu firm bracket Waterproof rate:IP68 Operating Environment:-40--+50°Celsius Anti-Fog design(military breather) Approval:CE/RoHS	\$11.99	149*86*64	12	13.2
9" 40W	AAL-1040			\$18.99	241.3*86*64	6	9.24
16" 80W	AAL-1080			\$33.99	419.1*86*64	6	15.36
23.5" 120W	AAL-1120			\$48.99	601.98*86*64	4	13.76
31.5" 160W	AAL-1160			\$64.99	784.86*86*64	4	18.08
37.5" 200W	AAL-1200			\$77.99	967.74*86*64	4	21.84
45" 240W	AAL-1240			\$94.99	1150.62*86*64	4	25.2
48" 260W	AAL-1260			\$101.99	1231.9*86*64	2	13.56

3 Rows LED Light Bar

12" 108W	AAL-3108		2side is normal reflector cup, Middle is 5S lens 3W/PCS Philips Voltage: 9-36 V DC Beam type: Combo beam LED color temperature: 6000-6500K Working life: 50,000 hours Waterproof rate: CE,RoHS,IP67 Working temperature: -40~ 85°C	\$14.99	305*73*107	4	9
20" 189W	AAL-3189			\$25.99	505*73*107	4	13
23" 219W	AAL-3216			\$29.99	584*73*107	4	15
26" 243W	AAL-3243			\$32.99	654*73*107	4	16.5
28" 270W	AAL-3270			\$36.99	723*73*107	4	18
31" 297W	AAL-3297			\$40.99	793*73*107	4	19
36" 351W	AAL-3351			\$47.99	932*73*107	4	21
45" 432W	AAL-3432	\$58.99	1140*73*107	4	25		
13.5" 144W	AAL-3144H		1w high intensity 3030 LEDs Operating Voltage: 10-30V DC Waterproof rate: IP 67 Optional Color: Black,White Color Temperature: 6000K Material:Diecast aluminum housing Lens material: PC Mounting Bracket: Alu firm bracket Beam:Combo 30000 hours above life time	\$18.99	352.42*77*68.54	6	14.3
21.5" 240W	AAL-3240H			\$27.99	557.02*77*68.54	6	20.7
31.5" 360W	AAL-3360H			\$40.99	812.22*77*68.54	4	19.1
41.5" 480W	AAL-3480H			\$53.99	1067.42*77*68.54	4	24.5
50" 576W	AAL-3576H			\$59.99	1071.42*77*68.54	4	28.4
51" 600W	AAL-3600H			\$61.99	1322.52*77*68.54	4	31
21.5" 192W	AAL-W192	 <p>3W CREE LED LIGHT BAR</p> <p>3 Rows Flood Reflector Cup Spot Reflector Cup 5S Flood Lens 2 Rows</p>	2 Rows by each side, 3 Rows in the middle Operating Voltage: 10-30V DC Waterproof rate: IP 67 3W/PCS Philips Optional Color: Black,White Color Temperature: 6000K Material:Diecast aluminum housing Lens material: PC Mounting Bracket: Alu firm bracket Beam:Combo 30000 hours above life time	\$26.99	60.5*13*15.2cm	6	20.7
31.5" 312W	AAL-W312			\$36.99	86*13*15.2cm	4	19.1
41.5" 432W	AAL-W432			\$45.99	112*13*15.2cm	4	24.5
50" 480W	AAL-W480			\$55.99	132.2*13*15.2cm	4	28.4
51" 504W	AAL-W504			\$57.99	137.5*13*16cm	4	31


6D Philips LED Light Bar(If you need Light Sensor,the unit price is \$15/pcs)

13.5" 120W	AAL-X120		6D Lens Operating Voltage: 10-30V DC 5W PHILIPS LEDs Waterproof rate: IP 67 Optional Color: Black,White Color Temperature: 6000K Material:Diecast aluminum housing Lens material: PC Mounting Bracket: Alu firm bracket Beam:8"Spot,15"Flood,Combo. 30000 hours above life time	\$19.99	357.5*86.5*111.2	6	14.3
21.5" 200W	AAL-X200			\$32.99	561.5*86.5*111.2	6	20.7
31.5" 300W	AAL-X300			\$49.99	816.5*86.5*111.2	4	19.1
41.5" 400W	AAL-X400			\$66.99	1071.5*86.5*111.2	4	24.5
50" 480W	AAL-X480			\$80.99	1275*86.5*111.2	4	28.4
51" 500W	AAL-X500			\$83.99	1325.62*86.5*111.2	4	31
52" 520W	AAL-X520			\$86.99	1427.62*86.5*111.2	4	32.7

Mixed White and Orange Remote Contorl LED Light Bar(EMC)


7.5" 36W	AAL-Q036		3W Cree + 0.5W each LED Operating Volt: 10-30Volt DC Color temperature: 6000K Operation temperature -40°C~60°C Waterproof rate: IP67 Beam: combo beam Material: Diecast aluminum housing Mounting Bracket: Alu firm bracket LENS: PC About 30000 hours life time Housing color: Black Remoter Instructions:50m Wireless remote distance 6 flash beam pattern optional A:switch on white color; B:switch on amber color; C:Press 1st:fast flashing of white color; Press 2nd:slow flashing of white color; Press3rd:SOS of white color; Press 4th: fast flashing of amber color; Press 5th:slow flashing of amber color; Press 6th: SOS of amber color D:Switch off	\$23.99	271.1*86.5*111.2	6	9
13.5" 72W	AAL-Q072			\$37.99	424.1*86.5*111.2	6	13
22" 120W	AAL-Q120			\$58.99	628.1*86.5*111.2	6	19.5
33" 180W	AAL-Q180			\$75.99	883.1*86.5*111.2	4	19
42" 240W	AAL-Q240			\$94.99	1138.1*86.5*111.2	4	24
50" 288W	AAL-Q288			\$125.99	1343*86.5*111.2	4	28.5
51" 300W	AAL-Q300			\$129.99	1385.2*86.5*111.2	4	31

OEM YOUR LOGO LED Light Bar (Design Logo Extra Charge)

13.5" 120W	AAL-Y120		5W each Philips LEDs OEM your Logo at two side,flash. Operating Voltage: 10-30 DC Waterproof rate: IP 67 Body Color: Black,White Color Temperature: 6000K Material:Diecast aluminum housing Lens material:PC LENS Mounting Bracket: Alu firm bracket Beam:combo. 30000 hours above life time	\$28.99	357.5*86.5*111.2	6	14.3
21.5" 200W	AAL-Y200			\$38.99	561.5*86.5*111.2	6	20.7
31.5" 300W	AAL-Y300			\$51.99	816.5*86.5*111.2	4	19.1
41.5" 400W	AAL-Y400			\$70.99	1071.5*86.5*111.2	4	24.5
50" 480W	AAL-Y480			\$81.99	1275*86.5*111.2	4	28.4
51" 500W	AAL-Y500			\$83.99	1325.62*86.5*111.2	4	31

OEM LOGO RGB light bar

Bluetooth APP RGB LED Light Bar


13.5" 72W	AAL-V072	 <p>Lighting control app showing color selection and brightness controls.</p>	RGB Bluetooth Remote Control 3W each CREE LEDs Operating Voltage: 10-30 DC Waterproof rate: IP 67 Body Color: Black,White Color Temperature: 6000K Material:Diecast aluminum housing Lens material:PC LENS Mounting Bracket: Alu firm bracket Beam:Combo. 30000 hours above life time	\$28.99	271.1*86.5*111.2	6	9
21.5" 120W	AAL-V120		\$39.99	424.1*86.5*111.2	6	13	
31.5" 180W	AAL-V180		\$53.99	628.1*86.5*111.2	6	19.5	
41.5" 240W	AAL-V240		\$69.99	883.1*86.5*111.2	4	19	
50" 288W	AAL-V288		\$79.99	1138.1*86.5*111.2	4	24	
51" 300W	AAL-V300		\$82.99	1343*86.5*111.2	4	28.5	

DIY 160000 Colors by phone APP


3W Philips LEDS TWO ROWS STRAIGHT LED LIGHT BAR

4" 18W	AAL-6018		3W each Philips LEDs Operating Volt:10-30Volt DC Color temperature:6000K Operation temperature -40°C~60°C Waterproof rate:IP67 Beam:30°spot beam,60°flood beam,combo Material:diecast aluminum housing Mounting Bracket:stainless steel bracket. LENS:PC LENS 30000 hours above life time	\$3.99	130.5*80*65	12	9
6.5" 36W	AAL-6036		\$5.99	232.51*80*65	12	12.12	
9" 54W	AAL-6054		\$8.99	334.71*80*65	12	15.84	
12" 72W	AAL-6072		\$10.99	436.72*80*65	6	10.8	
18" 108W	AAL-6108		\$12.99	589.53*80*65	6	15.3	
22" 126W	AAL-6126		\$14.99	640.7*80*65	6	16.98	
23" 144W	AAL-6144		\$16.99	844.71*80*65	4	10	
32" 180W	AAL-6180		\$21.99	946.73*80*65	6	24.7	
36" 234W	AAL-6234		\$27.99	1048.71*80*65	4	20	
45" 288W	AAL-6288		\$33.99	1253.71*80*65	4	22	
4" 18W	AAL-6018D		3W each Philips LEDs Operating Volt:10-30Volt DC Color temperature:6000K Operation temperature -40°C~60°C Waterproof rate:IP67 Beam:30°spot beam,60°flood beam,combo Material:diecast aluminum housing Mounting Bracket:stainless steel bracket. LENS:PC LENS 30000 hours above life time	\$3.99	130.5*80*65	12	9
6.5" 36W	AAL-6036D		\$6.99	232.51*80*65	12	12.12	
9" 54W	AAL-6054D		\$9.99	334.71*80*65	12	15.84	
12" 72W	AAL-6072D		\$11.99	436.72*80*65	6	10.8	
18" 108W	AAL-6108D		\$14.99	589.53*80*65	6	15.3	
22" 126W	AAL-6126D		\$16.99	640.7*80*65	6	16.98	
23" 144W	AAL-6144D		\$19.99	844.71*80*65	4	10	
32" 180W	AAL-6180D		\$24.99	946.73*80*65	6	24.7	
36" 234W	AAL-6234D		\$31.99	1048.71*80*65	4	20	
45" 288W	AAL-6288D		\$38.99	1253.71*80*65	4	22	


10W CREE LEDS SINGLE ROW MIXED COLOR LED LIGHT BAR

6" 30W	AAL-M030		<p>It can choose all white, all amber, or mixed color EMC</p> <p>CREE LED Each 10W/PC Operating Volt: 10-30Volt DC Color temperature: 6000K Operation temperature -40°C~60°C Waterproof rate: IP67 Beam:8°spot beam, 25°flood beam and combo beam Material: Diecast aluminum housing LENS: toughened glass Housing color: Black About 50000 hours life time</p>	\$14.99	152*103*56	12	14.8
11.5" 60W	AAL-M060			\$21.99	287*103*56	12	24.4
16.5" 90W	AAL-M090			\$28.99	422*103*56	6	17.5
22" 120W	AAL-M120			\$36.99	557*103*56	6	22.3
27" 150W	AAL-M150			\$43.99	692*103*56	6	26.1
33" 180W	AAL-M180			\$51.99	827*103*56	4	20.3
38" 210W	AAL-M210			\$58.99	975*103*56	4	24.3
43" 240W	AAL-M240			\$66.99	1097*103*56	4	28.5
48" 270W	AAL-M270			\$73.99	1232*103*56	4	31.7
50" 300W	AAL-M300			\$81.99	1367*103*56	4	33.8


3W HIGH/LOW BEAM LED Light Bar

14" 72W	S03-72W		3W high intensity CREE LEDs Operating Voltage: 10-30V DC Waterproof rate: IP 67 Optional Color: Black,White Color Temperature: 6000K Material:Diecast aluminum housing Lens material: PC Mounting Bracket: Alu firm bracket Beam: High/Low 30000 hours above life time	\$30.28	207*74*91	4	8
20" 108W	S03-108W		\$45.42	360*74*91	4	9.6	
26" 144W	S03-144W		\$60.56	513*74*91	4	13	
32" 180W	S03-180W		\$75.70	666*74*91	4	16.4	
38" 216W	S03-216W		\$90.85	820*74*91	4	23	
44" 252W	S03-252W		\$105.99	1126*74*91	4	26.4	
50" 288W	S03-288W		\$121.13	1279*74*91	4	29.7	

5W HIGH/LOW BEAM LED Light Bar

14" 30W	S05-30W		5W high intensity CREE LEDs Operating Voltage: 10-30V DC Waterproof rate: IP 67 Optional Color: Black,White Color Temperature: 6000K Material:Diecast aluminum housing Lens material: PC Mounting Bracket: Alu firm bracket Beam: High/Low 30000 hours above life time	\$15.04	280*69.1*47.2	4	6.2
20" 60W	S05-60W		\$30.09	521*69.1*47.2	4	9.6	
26" 90W	S05-90W		\$45.13	762*69.1*47.2	4	13	
32" 120W	S05-120W		\$60.18	1001*69.1*47.2	4	16.4	

10W HIGH/LOW BEAM LED Light Bar

7.5" 40W	S10-40W		10W high intensity CREE LEDs Operating Voltage: 10-30V DC Waterproof rate: IP 67 Optional Color: Black,White Color Temperature: 6000K Material:Diecast aluminum housing Lens material: PC Mounting Bracket: Alu firm bracket Beam: High/Low 30000 hours above life time	\$19.41	184*74*91	4	8
14" 80W	S10-80W		\$38.82	337*74*91	4	9.6	
20" 120W	S10-120W		\$58.24	490*74*91	4	13	
26" 160W	S10-160W		\$77.65	643*74*91	4	16.4	
32" 200W	S10-200W		\$97.06	796*74*91	4	19.7	
38" 240W	S10-240W		\$116.47	900*74*91	4	23	
44" 280W	S10-280W		\$135.88	1103*74*91	4	26.4	
50" 320W	S10-320W		\$155.29	1256*74*91	4	29.7	